

RESTEK INNOVATION

# NEW Restek Electronic Leak Detector



CE

Why allow a  
tiny leak  
to become a  
**GIANT**  
problem?



Chromatography Products

[www.restek.com](http://www.restek.com)



# NEW Restek Electronic Leak Detector

Ever have a small leak turn into a costly repair?  
Protect your data and analytical column by using a Restek Leak Detector!

- Optimized sample flow path.
- A sleek, new ergonomic, hand-held design.
- Rugged side grips for added durability.
- Handy probe storage for cleanliness.
- Longer lasting battery, up to 6 hours of continuous use.
- Automatic shut-off capabilities.
- A convenient carrying and storage case.
- A universal charger set (US, European, UK and Australian plugs included).

Contact your local  
Restek representative to  
**order yours  
TODAY!**



Carrying/storage case included with purchase of unit.

Backed by a 1 year warranty, the new Restek Leak Detector will again set an industry standard for performance and affordability in a hand-held leak detector.

### Leak Detector Facts

Detectable Gases:	helium, nitrogen, argon, carbon dioxide, hydrogen
Battery:	Rechargeable Ni-MH internal battery pack (6 hours normal operation)
Operating Temp. Range:	32°-120°F (0°-48°C)
Humidity Range:	0-97%
Warranty:	one year
Certifications:	CE, Japan
Compliance:	WEEE, RoHS

### Limits of Detection


Gas	Minimum Detectable Leak Rate (atm cc/sec.)	Indicating LED Light Color
Helium	1.0 X 10 <sup>-5</sup>	Red
Hydrogen*	1.0 X 10 <sup>-5</sup>	Red
Nitrogen	1.4 X 10 <sup>-3</sup>	Yellow
Argon	1.0 X 10 <sup>-4</sup>	Yellow
Carbon Dioxide	1.0 X 10 <sup>-4</sup>	Yellow

### Restek's Competitive Advantage

	Restek Leak Detector	Agilent G3388A Leak Detector
Probe Storage	✓	
Ergonomic Design	✓	
Hand Grips	✓	
Optimized Sample Flow Path	✓	
Storage Case	✓	
LED Leak Strength Indicator	✓	
6-Hour Battery	✓	

Avoid using liquid leak detectors on a capillary system! Liquids can be drawn into the system.

**\*Caution:** The Restek Electronic Leak Detector is NOT designed for determining leaks in a combustible environment. A combustible gas detector should be used for determining combustible gas leaks under any condition. The Restek Electronic Leak Detector may be used for determining trace amounts of hydrogen in a GC environment only.



Soft-side storage case is ideal for storing your leak detector in smaller spaces such as your tool box.



Verify hard-to-reach leaks using the small probe adaptor.

Description	qty.	cat.#
Leak Detector with Universal Charger Set (US, UK, European, Australian)	ea.	22839
Soft-Side Carry/Storage Case	ea.	22657
Small Probe Adaptor	ea.	22658



Lit. Cat.# GNPC1078-INT

© 2008 Restek Corporation.

Restek U.S. • 110 Benner Circle • Bellefonte, PA 16823 • 814-353-1300 • 800-356-1688 • fax: 814-353-1309 • [www.restek.com](http://www.restek.com)

Restek France • phone: 33 (0)1 60 78 32 10 • fax: 33 (0)1 60 78 70 90 • e-mail: [restek@restekfrance.fr](mailto:restek@restekfrance.fr)

Restek Ireland • phone: 44 2890 814576 • fax: 44 2890 814576 • e-mail: [restekeurope@aol.com](mailto:restekeurope@aol.com)

Thames Restek U.K. LTD • phone: 44 1494 563377 • fax: 44 1494 564990 • e-mail: [sales@thamesrestek.co.uk](mailto:sales@thamesrestek.co.uk)

Restek GmbH • phone: +49 (0) 6172 2797 0 • fax: +49 (0) 6172 2797 77 • e-mail: [info@restekgmbh.de](mailto:info@restekgmbh.de)

